TECHNICAL CHARACTERISTICS

PBATXL1EEM

Bat XL


Pedestal


A wide range of possibilities. Our pedestals, with an extensive variety of options available, different size and shapes -square or round - and an endless number of finishes.

DESIGNED BY ONDARRETA TEAM



ondarreta





DIMENSIONS

70 cm x 70 cm x 72 cm
(27.6” x 27.6” x 28.3”)
[width x depth x height]

WEIGHT

52 kg (114.6 lb.)

PACKAGING

Base: 71 cm x 71 cm x 2 cm
(28” x 28” x 0.8”)
Column H36,5: 42 cm x 10 cm x 10,5 cm
(16.5” x 3.9” x 4.1”)

CERTIFICATION

Product tested under the European standard EN 161399:2013, category of general use L1.

ORIGIN

100% Made in Europe

DESIGN

Ondarreta Team

ondarreta







COMPONENTS

COLUMN

Material
90 mm (3.54") diameter and 2 mm (0.08") thick cold laminated St-37 quality steel tube.
Tensile Strength: 340-470 /mm2 (49,300-68,160 psi); Elastic Limit > 235 N/mm2 (32,080 psi); Elongation > 25%, Surface Hardness > 110 HB.

Finish

Colour epoxy.

BASE

Material
700 mm (27.6") side and 10 mm (0.4") thick St-37 steel sheet inspired in organic forms and cut by laser.

Finish

Colour epoxy.

TABLETOP SUPPORT

Material
Ø120 mm (4.7") and 16 mm (0.6") thickness steel cylinder (for glass worktops) or a 295 mm (11.6") side and 5 mm (0.2") thick square steel sheet (for other worktops).

Finish
Colour epoxy.

TABLETOP

Material
A variety of beechwood, laminate, glass, compact, indoor compact, porcelain and laminate + birch plywood surfaces.

Finish
As on sample card

METAL FINISHES

EPOXYS

Powder covering formulated with polyester resins, with good both mechanical and chemical properties, outdoor maximum resistance and noxious compounds free. Electrostatic application and oven curated at 200ºC (392ºF).

Technical Characteristics:
Thickness (ISO 2360): between 60 and 90 µm.
Adherence (ISO 2409): Grade: 0 (maximum adherence)